

# ATTACHMENT 8

## DUST CONTROL SIGN

**Prior to obtaining a permit for clearing and grubbing, stockpile, or rough grading, the applicant shall install a dust control sign on the property as indicated below. After installation of signage, inspection will be required. If you have any questions, please contact Jim Waters at (909) 477-2710 x4203.**

### GENERAL INFORMATION

- 1) Sign thickness should be 5/8 or 3/4 inch CDX laminated plywood board, overall size of 48"x96" (4 feet by 8 feet).
- 2) Signage must be located within 50 feet of each projection site entrance.
- 3) One sign is sufficient for multiple site entrances located within 300 yards of each other.
- 4) Text height shall be at a minimum as shown on right side of sign template below.
- 5) Sign background must contrast with lettering. Typically black text with white background.
- 6) The lower edge of the board must be a minimum of 6 feet and a maximum of 7 feet above grade.
- 7) The telephone number listed for the contact must be a local or a toll-free number and shall be accessible 24 hours per day.

### SIGNAGE INFORMATION

Empty Space
Developers Name
Project Name/Tract #####
IF YOU SEE DUST COMING FROM
THIS PROJECT CALL:
Name, Phone Number
If you do not receive a response, please call
The AQMD at 1-800-CUT-SMOG
Empty Space

### LETTERING SIZE

3
4
4
4
4
6
3
3
3

### Example of Signage

